DATA SHEET DESONO™ SUBLIME



APPLICATIONS

Retail Outlets · Bars and Restaurants · Hotels · Cafés and Bistros · Kiosks · Corporate Meeting Rooms

DESCRIPTION

The SUBLIME is an ultra compact passive 6.5" dual coil subwoofer that offers the ultimate blend of size and performance. It provides powerful, high-impact bass response to augment any combination of Desono full-range loudspeakers.

The thinnest subwoofer on the market at only 120 mm (4.7") wide, SUBLIME can be installed in a variety of locations: mounted on a wall, behind curtains, or even under furniture. Audio connections are hidden when mounted on the wall using the included brackets.

The SUBLIME subwoofer has a built-in stereo crossover, eliminating the need for external filters. Optionally, you can use the SUBLIME subwoofer in an active speaker configuration, using an active filter and separate power amplifier.

The Desono SUBLIME's clean, clear bass response provides a compelling audio experience for shoppers in retail environments as well as bar, pub, and restaurant patrons.

ULTRA COMPACT PASSIVE 6.5" SUBWOOFER

FEATURES

- Small footprint (only 4.7" [120 mm] wide)
- Clean, clear bass response
- Dual coil woofer for stereo operation
- Wall mountable (brackets included)
- Integrated crossover outputs for stereo satellite speakers
- Overload protection for 24/7 failsafe operation

TECHNICAL SPECIFICATIONS

Operating Mode	Passive
Operating Environment	Indoor
Operating Range (-3dB)	50 Hz to 200 Hz
Nominal Beamwidth (H x V)	Omnidirectional
Transducers	1 x 6.5" (165 mm) dual voice coil (treated paper cone)
Continuous Power Handling @ Nominal Impedance	18V 2 x 40W @ 8Ω (160W peak)
Nominal Sensitivity @ 1m	 @ 1W @ 2.83V 85 dB 85 dB
Nominal Maximum SPL @ 1m	PeakContinuous107 dB101 dB
Protection	3-step self-resetting protection
Recommended Amplifiers	40W - 80W @ 8Ω (19V - 27V) per input
PHYSICAL	
Input Connection	(4x) 5-way binding posts
Output Connection	(4x) 5-way binding posts
Mounting Provisions	Wall mount bracket
Environmental	IP20 per IEC 60529
Dimensions H x W x D	16.5" x 4.7" x 18.5" (420 mm x 120 mm x 470 mm)
Weight	17.6 lbs (8 kg)
Finish	Refer to the Technical Drawings (page 2)
Accessories (included)	Wall mount bracket; installation template

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice. Data presented on this spec sheet represents the basic performance specifications for the model. For a detailed analysis of this loudspeaker's performance, please download the GLL file from our website: biamp.com

biamp.

: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA T: +1 5

biamp.

TECHNICAL DRAWING / DIMENSIONS / FINISH

HxWxD

16.5" x 4.7" x 18.5" (420 mm x 120 mm x 470 mm)

Unit Weight 17.6 lbs (8 kg)

Shipping Weight 23.6 lbs (10.7 kg) Grille: Cloth White (RAL 9003) or Black (RAL 9011)

Enclosure / Finish MDF, matte finish, White or Black



